- 3. A combination as set forth in claim 2, wherein said surface further comprises at least an additional aperture at either end of said gemstones.
- 4. A combination as set forth in claim 3, wherein said connecting member comprises a tack with a head and a central pin depending therefrom.
- 5. A combination as set forth in claim 3 wherein said connecting member comprises a bar which straddles the gemstone.
- 6. A combination as set forth in claim 3 wherein said connecting member comprises a bar which straddles the gemstone.
- 7. A combination as set forth in claim 5 wherein said connecting member comprises a pair of bars so as to have each respective bar bear upon a respective gemstone set next to each other.
- 8. A combination as set forth in claim 2 wherein said connecting member comprises a bar which straddles the gemstone.
- 9. A combination as set forth in claim 2 wherein said connecting member comprises a pair of bars so as to have each respective bar bear upon a respective gemstone set next to each other.
- 10. A combination as set forth in claim 2 wherein said gemstones are connected to form a row of gemstones.
- 11. A combination as set forth in claim 2, wherein said sleeve is separate from said connecting member and is slid on said connecting member beneath said surface.
- 12. A combination as set forth in claim 1, wherein said item of jewelry is a pendant.
- 13. A combination as set forth in claim 12 wherein said is connecting member comprises a bar which straddles the gernstone.
- 14. A combination as set forth in claim 12 wherein said connecting member comprises a pair of bars so as to have each respective bar bear upon a respective gemstone set next to each other.
 - 15. A combination as set forth in claim 12 wherein said gernstones are connected to form a row of gernstones.
- 16. A combination as set forth in claim 12, wherein said sleeve is separate from said connecting member and is slid on said connecting member beneath said surface.
- 17. A combination as set forth in claim 1, wherein said surface further comprises at least an additional aperture at either end of said gemstones.
- 18. A combination as set forth in claim 17, wherein said connecting member comprises a tack with a head and a central pin depending therefrom.
 - 19. A combination as set forth in claim 17 wherein said connecting member comprises a bar which straddles the generating
- 20. A combination as set forth in claim 17 wherein said connecting member comprises a pair of bars so as to have each respective bar bear upon a respective gemstone set next to each other.
- 21. A combination as set forth in claim 1 wherein said connecting member comprises a pair of bars so as to have each respective bar bear upon a respective gemstone set next to each other.
 - 22. A combination as set forth in claim 1 wherein said gemstones are connected to form a row of gemstones.
 - 23. A combination as set forth in claim 1 wherein said connecting member comprises a bar and said pin comprises a pair of pins, wherein said at least an additional aperture

4 e 4

comprises two apertures through which said pair of pins in said connecting member pass to secure said gemstone to said item of jewelry.

24. A combination as set forth in claim 1, wherein said sleeve is separate from said connecting member and is slid on said connecting member beneath said surface.

25. A combination as set forth in claim 1, wherein said sleeve is integrally formed from the undersurface of said surface of said item of jewelry.

26. A combination as set forth in claim 1, wherein said 1 gemstone comprises an oval gemstone, said aperture com-

prises an oval shape, and said item of jewelry comprises a jewelry ring, wherein said apparatus connects a row of said oval gemstones onto the surface of said ring.

27. A combination as set forth in claim 1, wherein said stones comprise marquis stones, said item of jewelry comprises a jewelry ring, and said connecting members bear on the ends of said marquis stones to hold said stones in place on said jewelry ring.

The start , m 4.1

J--28. A combination of a gemstone, an item of jewelry and a connecting member to secure said gemstone to said item of jewelry, said combination comprising: said item of jewelry having a surface to which said gemstone to be secured; said gemstone having at least one end, an upper surface, a lower surface, and a girdle in-between, said surface of said item of jewelry comprising an aperture having an opening similarly shaped and slightly smaller than the girdle of said gemstone so that said lower surface of said gemstone projects through said aperture; said surface of said item of jewelry further comprising at least one additional aperture located adjacent said end of said gemstone; said connecting member comprising a pin extending downwardly through said additional aperture,

a sleeve located below said surface of

said jewelry item;

said connecting member being pushed
downwardly on said gemstone to hold
said gemstone in place, said sleeve being
cold soldered to said pin to secure said
connecting member in place.

- --29. A combination as set forth in claim 28, wherein said item of jewelry is a pendant.
- --30. A combination as set forth in claim
 29, wherein said connecting member
 comprises a bar which straddles the
 gemstone.
- --31. A combination as set forth in claim 28, wherein said item of jewelry is a ring.
- --32. A combination as set forth in claim
 31, wherein said connecting member
 comprises a bar which straddles the
 gemstone.

1—33. A combination of a gemstone, an item of jewelry and a connecting member to secure said gemstone to said item of jewelry, said combination comprising:

said item of jewelry having a
surface against which said gemstone is
secured;

end, an upper surface, a lower surface, and a girdle in-between, said surface of said item of jewelry comprising an aperture having an opening similarly shaped and slightly smaller than the girdle of said gemstone so that said lower surface of said gemstone projects through said aperture;

said surface of said item of
jewelry further comprising at least one
additional aperture located adjacent said
end of said gemstone;

said connecting member

comprising a pin extending downwardly

through said additional aperture;

said connecting member being

pushed downwardly on said gemstone to

hold said gemstone in place, said pin

being cold soldered to said item of

jewelry to secure said connecting member

in place.